

NEOTHERM INTELLIGENT INFANT WARMER IW4000 Series



IW4200W - Wall Mounted



IW4200S - Stand Warmer



**IW4100S - Stand Warmer
with Height Adjustment**



**IW4100S - Stand Warmer
with Detachable Trolley**

Heater Unit

Ceramic Heater with parabolic reflector

Swivels 90° on both sides

Inbuilt Observation Lamp

Monitor Tray

Capable of holding
up to 10 kg weight



More than two infusion
pumps can be clamped
on Stainless Steel Rod

IV Saline Stand Height
can be adjusted

Bassinet

Rectangular Trolley in Mild
Steel or Stainless Steel
construction with High
Grade Powder Coating

Unbreakable Polycarbonate
Drop-down and lock-able
side support

Easy Mattress Tilting in both
directions

X-ray Cassette facility can be
provided

**IW4100 - Neotherm
D10 Infant Warmer**

Lock-able Castor wheels

Strong Shelf

TECHNICAL SPECIFICATIONS

Dimensions

WIDTH	90 cm
DEPTH	110 cm
HEIGHT	185 cm
MATTRESS SIZE	70 cm x 50 cm x 4 cm
MONITOR TRAY SIZE	27 cm x 32 cm

Features

HEATER	Ceramic Heater - 650W
HEATER ROTATION	±90° on both sides
REFLECTOR	Parabolic Reflector
OBSERVATION LAMP	50W Hazzle Free Halogen lamp
MONITOR TRAY	ABS Plastic Molded
SIDE PANELS	Unbreakable Polycarbonate drop down
WHEELS	Strong Castor wheels with 2 brake
MATTRESS	Waterproof, Washable, Flame Resistant
MATTRESS FOAM DENSITY	21- 25 kg/m ³
IV POLE	Adjustable Height with two poles
INFUSION PUMP STAND	Stainless Steel rod
TEMPERATURE SENSOR	Thermistor based NTE Sensors with high resolution

Temperature Control

SUPPLY VOLTAGE	190V - 250 VAC
SUPPLY FREQUENCY	50 - 60 Hz
POWER CONSUMPTION	750W
TEMPERATURE DISPLAY	Celcius / Farnheit
TEMPERATURE RANGE	10°C - 50°C
TEMPERATURE RESOLUTION	0.1°C
TEMPERATURE ACCURACY	± 0.2°C
SET TEMPERATURE RANGE	30 - 38°C in 0.1°C increment
HEATER OUTPUT	0 - 100% in 1% increment
MODES OF OPERATION	Baby, Air, Manual
TIMER	0 to 99 min
MANUAL MODE TIMER	15 mins
ALARMS	Audio and Visual


Alarms

HIGH TEMPERATURE	If Temp > Set Temp + 1°C
LOW TEMPERATURE	If Temp < Set Temp - 1°C
OVERHEAT	If Temp > 38°C (Baby) / 39°C (Air)
SENSOR FAILURE	Sensor disconnection / not working
POWER FAILURE	If Power fails
BATTERY FAILURE	Rechargeable battery for power failure
SYSTEM FAILURE	If system hangs
HEATER FAILURE	If Heater stops working

NEOTHERM Control

Computerized Software Based PID Servo Control System. PID is the most advanced servo control system which considers even smallest change in temperature

IW4100 - Neotherm D10



Skin Temperature Display
Modes: Auto, Manual
Display: Segment LED
Heater % Display: Bar Graph

IW4200 - Neotherm D20



Skin & Air Temperature Display
Modes: Baby, Air, Manual
Display: Segment LED
Heater % Display: Bar Graph

IW4300 - Neotherm iLCD



Skin & Air Temperature Display
Modes: Baby, Air, Manual
Display: Graphic LCD Display
Temperature Trends, Realtime clock, Programmable Timers

IW4400 - Neotherm iWarm



Skin & Air Temperature Display
Modes: Baby, Air, Manual
Display: 5.6" Color TFT Screen with touch screen
Temperature Trends, Realtime clock, Programmable Timers

* AVI Healthcare Pvt Ltd reserves right to make changes without notice in design, specifications and models

Manufactured by:



Manufacturing Neonatal Equipments "Glocally"

ISO 13485:2016
CERTIFIED COMPANY



Address : 25, Nanddeep Industrial Estate, Kondivita Lane,
Andheri East, Mumbai - 400059, Maharashtra, India
Telephone : +91 22 28320452/ +91 22 28326240
Email : sales@avihealthcare.com

Tested as per following EC standards:
EN 60601-1:2006/A1:2013
EN 60601-1-2:2015
EN 60601-1-6:2010
EN 60601-1-8:2007/A11:2017
EN 60601-1-2-21:2009